

Application Catalogue

Measuring instruments and testers



www.metrel.si

About Us

METREL has a long and rich history of making innovative test and measurement solutions. It was established in 1957 as a factory for the production of test and measurement equipment for the domestic market. It quickly grew from there into a major international player in the field of testing.

All research and development of new products and their manufacturing takes place in a single location. This enables tighter control over quality, and faster responsiveness to market demands, which have shaped our product portfolio, consisting of multifunctional electrical safety testers for the electrical industry with a growing number of specialized solutions for renewables and e-mobility.

Solutions that are available through our business partners in more than 80 countries worldwide and are presented in this application catalogue.



Metrel has introduced a range of Certified Training Modules based on, and adjusted to comply with, the EU-countries industry standards

The necessary equipment

Metrel's Safety and Quality Tester Instruments cover the needs of installers, constructors, planners and inspectors. Each tester supports test procedures and measuring methods according to the main standards and other regulation. The Test instruments represent a strong tool for troubleshooting, testing, diagnosing and reporting.

Advanced Features and several key solutions are specifically highlighted with regard to the competitors' solutions.

Applications and Solutions can be found in a number of additional operation and Good to Know documents related to the relevant industry sectors.

Certified Training Modules and **Seminars** are supported by the **Metrel Academy**. Within the Knowledge section we make recommendations and suggestions in support of national vocational qualification schemes. We can also offer training with completely new Training Modules for new application areas.

SOLID KNOWLEDGE BASE

Metrel is continuously investing in developing the R&D working groups, which leads to new product solutions and improved technical and application knowledge. We are pleased to say that a number of our design engineers and product managers have thoroughly developed their technical knowledge and application experience about different markets for our products, so we can proudly state that we are Experts in our Field.

Metrel works in co-operation with important external organizations and institutions like:

- IEC Technical Committees and their Working Groups
- Faculties of Electrotechnics at different Universities
- Electrotechnical Associations
- Engineering Associations
- Electrical Safety Boards
- Chambers of Engineers
- Chambers of Commerce and Industry
- Chambers of Craft and Small Business

PARTNERSHIP

Metrel is cooperating closely with important associations and committees related to its industry sectors and is a member of the Slovenian Institute for Standardization. We have individuals who participate in several technical committees, as well as internationally in IEC Technical Committees. Metrel is also involved in the Committee for the Electrotechnical Safety and Low-voltage electrical installations (NNELI) as a partner company through the »eTest scheme« in Slovenia. We are a partner company of the E-Check Association of electrical installers in Germany and cooperate with similar associations in other countries.



REFERENCES

Through our own participation in providing and supporting national vocational qualification programs in the field of electrical safety during the past decades, and through our close collaboration with professionals from various industries, at Metrel Academy we are aware of the importance to continuously develop knowledge and new skills through various levels of training and qualification programs. This ensures self-confidence of the workforce in companies involved with Electrical Safety, it boosts their competitiveness, and enables safe and profitable working processes of their customers.

Metrel's participation in preparation of curricula for electrical engineering in Slovenia includes the following:

- Preparation of the Knowledge and Skills catalogue
- Giving assistance in defining qualification requirements list for the candidates in the vocational qualification program
- Preparation of the Assessment Exams catalogue

Metrel also assists experts working on the vocational qualification programs through its distribution – partners' network worldwide. This has been mostly related to the application of Metrel test and measurement instruments.

CERTIFIED TRAINING MODULES

Certified Training Modules and Seminars are supported with packages of printed Handbooks, White paper, Exercises, Quick Guide Charts, and Posters together with other elements of Application and Technical Support. All low voltage training modules can be performed on Metrel's application trainer.

MODULE PACKAGES

E-HANDBOOKS, QUICK GUIDE CHARTS, and EXERCISES about measuring and testing based on the International / European Standardization for every participant.



Wall Posters

 Wall posters visually represent typical testing and measurement procedures and / or troubleshooting tasks, or a list of required customized tests in certain areas of application.

Scope of Application & Technical Support

- Demonstration Equipment
- Testing instruments
- Power Point Presentations on product solutions
- On-line Technical Support: any inquires related to Metrel products can be sent to the following email addresses:
 - info@metrel.si
 - info@metrel.co.uk
 - info@metrel.de
- Bespoke product training for an individual customer or larger groups of people
- Complete distributor set-up training (product, repair, and calibration training)
- B2B web support provides specific technical information for Metrel partners
- Download centre enables you to download files with technical product information

Contents

QUALIFICATION CERTIFICATE

European Qualification Certificate adjusted to the EUcountries industry standards ensures the competency of individual participants who pass the final Exam on Theoretical and Practical knowledge for the specific locally approved Training Module.

Know-How Package - for a Transparent Localization Process Knowledge Catalogue - for the specific Training Module for modification to a local - National regulation. **Exams Catalogue -** with the definition of the minimum level of the Entry conditions for a participant. **Approved Certificate -** approval of the obtained qualification when signed by a local authorized organization like:

- Training organization
- Electrical Safety Board Organization, e.g. NNELI etest / local – National AIE partner

Metrel Academy has put out a comprehensive list of training sessions in order to help you master the latest measurement and testing technologies.

hicles / Mobile unit w.metrel.si

ELECTRICAL INSTALLATION SAFETY

- LV Installation Safety & Industry Machine & EVSE & Operation Condition Quality & Switchboards & Circuit Protection Parts
- PV Systems, Inverters, Panels, Modules Testing, Maintenance, Troubleshooting
- EV safety testing & EVSE safety and functional testing
- Special Installations Testing, Maintenance, Troubleshooting, Airports, Railway, Industry
- Special Installations Testing, Maintenance, Troubleshooting & Integrated IT Systems

est	APPLIANCE/MACHINE/SWITCHBOARD SAFETY	14 - 15	
l	 Portable Appliances Safety Testing, CE Marking & Machines Electrical Safety & Switchboards Safety Medical equipment, medical systems, surgery room IT installation 		
	POWER QUALITY ANALYSIS	16 - 17	
	Power and Voltage Quality & Consumption & Disturbances		
	HV INSULATION/CONTINUITY/EARTH/TRANSFORMER/IMPEDANCE	18 - 19	
l	 HV Safety and Quality in Industrial Systems & Power Generation & Distribution Systems & Construction Sites 		
	MULTIMETERS / CLAMP METERS / VOLTAGE TESTERS / THERMAL CAMERAS	20 - 21	
l	 General / basic testing up to high level industrial testing, electronic fault finding, field servicing and heavy duty electrical testing 		
	PC SOFTWARE	26 - 27	
	Electrical Installation Safety HV Safety Portable Appliance Testing Power Quality		

Electrical Installation Safety, HV Safety, Portable Appliance Testing, Power Quality Analysis and multimeter Windows Software and Android Apps

4 - 11

LV Installation Safety & Industry Machine & EVSE & Operation Condition Quality & Switchboards & Continuity, Insulation, Z Loop impedance, RCD, Earth...



GENERAL FEATURES

- Predifined and/or programmable AUTO SEQUENCES. Automatic LIVE and DEAD tests, programmable, no lost or forgotten results / parameters, worst case evaluated, human error factor minimized;
- Automatic evaluation of safety at test point, up to 50 parameters, Fuse and RCD characteristics, adjusted and custom limits and tested results combined together and evaluated simply as PASS / FAIL;
- Report Creator with powerful two way communication PC SW Tool MESM or EuroLink PRO;
- Up to 5 times faster than any existing equivalent Safety testing procedure.

ADVANTAGES

- **TN / TT / IT** and other earthing systems support;
- 3- and 4-wire Zloop (L-PE) and Zline (L-N and L-L) impedances at entry and exit points of circuits, comparison of both results and △U calculation in %, Ipsc and Ipfc calculation, Fuse protection evaluation;
- Uc, Zline & Zloop tests kombined into one automated impedance testing procedure (Z AUTO);
- Automated RCD testing procedure (RCD AUTO);
- Contact voltage measurement with P/S probe;

- Test of RCD protection at AC / A / F / B / B+ / MI RCD / EV RCD current shape on G or S type;
- Evaluation of PE continuity, automatic polarity switch;
- PE resistance evaluation;
- Insulation testing (Switchboard, Circuits, Insulation of Walls and Floors, Antistatic Floors, Automatic insulation testing);
- PI / DAR calculation;
- Varistor test;
- TRMS Clamp-on Leakage Current testing;
- Over voltage protection with ramp;
- IMD and ISFL testing on IT systems, Medical site testing, Mobile Installations;
- Test of IMD, ELM and RCM devices with ISFL pretest and Voltage balance evaluation;
- Earth / Ground resistance testing: 2-wire, 3-wire, 4-wire (option), 1 clamp, 2 clamps;
- Functional inspections;
- EVSE AUTO SEQUENCEs and functional inspections;
- Machine functional and visual inspections;
- Measurement filtering by selected area group;
- Other tools for Three Phase Systems, Locating fuses and cables, Illumination measuring, high resolution Z impedance for power lines, QR and/or barcode scanner support;
- PC SW (Metrel ES Manager) and Android (aMESM) support.



Circuit Protection Parts Selection Guide

APPLICATION	FEATURES	Description	MI 3155 EurotestXD	MI 3152 EurotestXC	MI 3152H EurotestXC 2,5 kV	MI 3102 BT EurotestXE	MI 3102H BT EurotestXE 2,5kV	MI 3100 SE EurotestEASI	MI 3125 BT EurotestCOMBO
 Testing of TT, TN and IT systems; Testing of single and multiphase systems; Initial and periodic testing and inspections of domestic and industrial installations;))		
 Low Voltage Electrical Installation Safety testing; 	AUTO SEQUENCES	Programmable AUTO SEQUENCEs	•						
Electrical Safety in Working places;	·	Pre-programmed AUTO SEQUENCEs	•	•	•				
Electrical Safety in Public Areas;	AUTO TEST	Auto TT (U, Zln, Zs, Uc)	•	•	•	•	•	•	
		Auto TN/RCD (U, Zln, Zs, Rpe)	•	•	•	•	•	•	
 Fire Safety and Hazards, Troubleshooting of 		Auto TN (U, ZIn, ZIp, Rpe)	•	•	•	•	•	•	
overloaded electrical systems, hot wiring or		Auto IT (U, ZI, Is, Im)	•	•		•			
connections, failed components;	VOLTAGE	Voltage TRMS, Frequency	•	•	•	•	•	•	•
Maintenance (Low Voltage installations		1-phase / 3-phase support	• / •	• / •	• / •	• / •	• / •	• / •	• / •
maintenance. Preventive and Predictive		Low & high limit /Un setting	•/•	•/•	• / •				
		Phase SEQUENCE L1-L2-L3	•	•	•	•	•	•	•
maintenance, Corrective maintenance / Reactive	INSULATION	50 V - 1 kV / 2,5 kV PI DAR	•/•	• / -	• / •	• / -	•/•	• / -	• / -
repairs);		Auto L-PE, N-PE, L-N	•						
 Lightning installations; 	CONTINUITY	Rlow (200mA) / 4-wire	• / •	• / -	• / -	• / -	• / -	• / -	• / -
 Testing on high and low frequency installations 		Continuity (7 mA)	•	•	•	•	•	•	•
	RPE	RPE / RPE (RCD)	16 400 Hz	45 65 Hz	45 65 Hz	45 65 Hz	45 65 Hz	45 65 Hz	45 65 11
(industrial, aircraft, railway, mining, chemistry, ferry	ZLINE	Zline, Ipsc, ΔU% / FUSE tables	16 400 Hz	45 65 Hz	45 65 Hz	45 65 Hz	45 65 Hz	45 65 Hz	45 65 Hz
boat);	ZLOOP	3- wire / 4-wire	• / • 16 400 Hz	• / -	• / -	• / - 45 65 Hz	• / - 45 65 Hz	• / - 45 65 Hz	• / -
 Construction sites; 	ZLUUP	Zloop, Ipfc / FUSE tables Zs(rcd)	• / •	45 65 Hz • / -	45 65 Hz	45 65 HZ	45 65 HZ	45 65 HZ	45 65 Hz • / -
Mobile LV Generator Units:	RCD	3- wire / 4-wire RCD t, Uc, RCD I ramp, Uc, Auto	•/• AC/A/B/F/B+	•/- AC/A/B/F/B+	• / - AC / A / F	•/- AC/A/B/F/B+	•/- AC/A/F	• / - AC / A / F	•/- AC/A/B/F/B+
 Facility Management, maintenance and care of 	RCD	MI RCD, EV RCD / PRCD-S, PRCD-K	•/•	•/•	•/•	•/•	AL/A/F	•/-	•/-
	EARTH	Earth 3W	• / •	• / •	•	•	•	• / =	• / =
commercial or institutional buildings, such as	LARIN	Earth 2 Clamps	Optional	Optional	Optional	Optional	Optional	-	-
hospitals;		RO adapter	Optional	Optional	Optional	Optional	Optional		
 Hotels, office complexes, arenas, schools or 	OTHER	Power (S, Q, PF, THDU)	•	•	•	•	•		
convention centers:	OTTER	Harmonics (U, I)	•	•	•	•	•		
		Current Leakage / Load	•	•	•	•	•		
 Machine and switchboard testing; 		IT support / IMD, ISFL	•/•	• / •		•/•		• / -	• / -
 Medical installation testing; 		Varistor	•	•	•	,		1	
 Fire brigades, ambulance, military and police 		PI / DAR calculation	•		•				
vehicles:		Area groups	•	•	•				
 Mobile Video/Audio, Concert Halls, Fairs, 		Commanders	•	•	•	•	•	Optional	Optional
		EVSE	Optional (full)	Optional (full)	Optional (full)	Optional	Optional	Optional	Optional
Playgrounds;		Locator	Optional	Optional	Optional	Optional			
 Electrical Vehicle Supply Equipment (EVSE) testing; 		LUX Sensor	Optional	Optional	Optional	Optional	Optional		
 Observation of insulation trends. 		Ring (UK installations)	Optional	Optional	Optional	Optional	Optional	Optional	Optional
	PC SW MESM	BASIC license / PRO license	 / Optional 	 / Optional 	 / Optional 	 / Optional 	 / Optional 	 / Optional 	 / Optional
		RS232 / USB / Bluetooth	•/•/•	•/•/•	•/•/•	•/•/•	•/•/•	• / • / Optional	• / • / •
	PORTS & PC FEATURES	Work space manager	•	•	•				
	FEATURES	Memory /SD card	8 GB / • (removable)	8 GB / •	8 GB / •	4/1800	4 /1800	4/1800	4 /1700
		Colour touch screen	•	•	•				
	GENERAL DATA	IP protection	IP 56	IP 40	IP 40	IP 40	IP 40	IP 40	IP 40
		Batteries	4.4 Ah Li-Ion	6 x AA	бх АА	бх АА	6 x AA	6 x AA	6 x AA

PV Systems, Inverters, Panels, Modules Testing, Maintenance, Troubleshooting Photovoltaic Modules, Panels, Strings, Inverters...



GENERAL FEATURES

- Automatic measurements on PV Systems.
- Combined photovoltaic tester and electrical installation safety tester.
- Environment measurements and calculation to STC.
- Insulation measurements under energised PV system.
- Large PV module Data Base;
- PASS/FAIL evaluation of electrical safety test results;
- Report Creatorr with powerful two way communication PC SW Tool EuroLink PRO and Metrel ES Manager

ADVANTAGES

PV installation testing:

- Uoc, Isc, Irradiance and Temperature measurements;
- I U curve of modules and strings on PV systems;
- Real time environment data measurement with wireless remote unit;
- MPP determination and STC calculations;
- Irradiance and Temperature Logger;
- Insulation under Voltage of PV panels and strings;

Power measurements on AC and DC:

- DC / AC TRMS Clamp-on Current testing;
- Efficiency of Solar Panels and Inverters;
- Electrical Safety testing:
- Zloop L-N and L-L, RCD protection;
- **Continuity** and Earth Bond test;



- Over voltage protection testing;
- Earth / Ground resistance testing;
- TRMS Clamp-on Leakage Current testing.

- Testing of PV generator with max system voltage up to 1500 V $\,$
- Safety testing of PV and electrical installations.
- Measuring and Testing the Efficiency of the whole System.
- MPP check, Inverter check, Working point of Inverter Testing.
- Maintenance and troubleshooting based on I-V characteristic checking for possible deviations from the standard shape.

FEATURES	Description	MI 3115 PV Anayser <mark>NEW</mark>	MI 3108 EurotestPV	MI 3109 EurotestPV Lite	A 1785 PV Remote WL	A 1378 PV Remote
LECTRICAL	Insulation resistance up to 1500 V	•				
NSTALLATION SAFETY	Insulation resistance up to 1000 V		•	•		
	Continuity 200 mA	•	•	•		
	Line / Loop Impedance		•			
	RCD A, AC, B		•			
	Earth resistance		•			
	Rotary field		•			
V GENERATOR	lsc, Uoc	1500 V / 20 A	1000 V / 15 A	1000 V / 15 A		
IEASUREMENTS	Automatic test sequence	•		•		
	I-V curve	•	•	•		
	Umpp, Impp, Pmax	•	•	•		
	Extrapolation to STC	•	•	•×		
	Rs (calculated in PC SW)	•	•	•		
NVIRONMENT	Irradiance		•	• ×	•	•
IEASUREMENTS	Module temperature		•	• ×	•	•
	Logger				•	•
	Wireless	•			•	
V SYSTEM POWER	DC side measurements U, I, P		•	•		
IEASUREMENTS	AC side measurements (single phase) U, I, P		•	•		
	Single phase PV and inverter energy conversion efficiency		•	•		
	Three phase PV and inverter energy conversion efficiency		Option**	Option**		
XTENDED POWER	P, Q, S, THDU, PF/cos fi		•			
UNCTIONALITY	AC/DC current		•			
	Scope function		•			
	Energy		•			
	Harmonics (up to 11 th)		•			
TANDARD/	Tip Commander		Option			
PTIONAL	Remote unit (logger)	•	Option	Option		
CCESSORIES	PV safety probe		•	Option		
	MC4 adaptors	•	•	•		
	AC/DC current clamp		•	•		
	PV reference cell	•	•	Option		
	Temperature probe	•	•	Option		
PC SW	Metrel ES manager	•	•	•		
	PC SW EuroLink PRO Plus		•	•		

* Environment data can be entered manually or measured with optional accessory. ** Three phase PV efficiency can be measured by synchronisation with any Metrel Power Analyser.

EV safety testing & EVSE safety and functional testing EV testing, Mode 3 EVSE, Mode 2 EVSE. Mode 3 cables...



GENERAL FEATURES

- Insulation measurements according to UN ECE R100 and ISO 6469-3 with own REESS as DC voltage source;
- Insulation resistance with DC voltage from 50 V to 1500 V;
- DC and AC TRMS voltage and frequency measurements;
- Four wire Micro Ohm measurements with 2 A DC test current;
- Banana socket outputs for connection to a 3-phase installation tester;
- Voltage indicators on EVSE output;
- Proximity Pilot resistance selector for simulation of EV cable presence and current rating detection;
- Control Pilot resistance selector for simulation of electric vehicle status;
- Type 2 Male Plug connector for connection to EVSE;
- EV and EVSE AUTO SEQUENCE® support;
- MESM report creation with installation testers;
- Load testing up to 13 A on socket 1 phase or on banana sockets - 3 phase;
- Fault simulation of Diode short, PE-CP short and PE open on the output and errors on the input;
- Output for CP signal monitoring.

ADVANTAGES

• EV safety testing and designed especially for electric vehicle testing. The instrument support the latest standard UN ECE R100 and ISO 6469.

- With programmable AUTO SEQUENCEs the work can be repetitive and safe.
- The complete EVSE safety test program supported by the latest installation testers can be tested accurate and with ease.
- The diagnostic test for EVSE can interpret the PWM communication signal for better understanding the EVSE behaviour.
- Preprogrammed visual test for the safety of the operator and for the user.

- EV safety tests;
- Electric vehicle high voltage cables insulation and resistance test;
- Battery insulation check according to UN ECE R100;
- EV chassis and components bonding test;
- EVSE functional and diagnostic testing according to EN 61851-1 and electrical safety testing according to EN 60364-6.
- On-site testing of EVSE charging station installation;
- Initial and periodic testing of private, semi-private and public EVSE charging stations.
- Electrical safety testing of 1-phase and 3-phase Mode 2 EV cables
- Simulation of faults on mains for verification of Mode 2 electrical vehicle (EV) charging cable safety features.
- Electrical safety testing of Mode 3 EV cables on PTI and workshops.



COMPLETE EVSE TESTING SOLUTION

The combination of A 1632 or A 1532 (XA) with Metrel's installation testers the MI 3155 or MI 3152 offers a complete solution for testing in circuits with an EV RCD or EV RCM 6 mA d.c. trip-out protection. It is possible to perform a compete RCD test sequence including the 6 mA d.c. ramp test and loop impedance (Zs rcd) measurement without tripping 6 mA d.c. EV RCD or EV RCM. This makes Metrel compliant with standards IEC 61851-1 (EVSE General requirements), IEC 62572 (Mode 2 charging) and EN 62955 (RDC-DD). Complete with A 1832 Mode 3 Charging cable adapter, that offers the simplest way to test the Mode 3 cables with MI 3365, MI 3132 or installation testers like the MI 3155 and MI 3152.

FEATURES	Description	MI 3132 EVTester NEW	A 1532 XA EVSE adapter	A 1532 EVSE adapter	A 1632 eMobility Analyse	A 1631 r EV monitoring cable	A 1832 EV monitoring cable NEW
							8
AUTOSEQUENCES	AUTOSEQUENCE Programmable	•					
	Pre-programmed AUTO SEQUENCEs	•					
INSULATION	EV R100	•					
	50 V - 1.5 kV	•					
RESISTANCE	2 Wire 10 mA - 2 A	•					
	4 Wire 10 mA - 2 A	•					
VOLTAGE	TRMS AC	•			•		
	DC	•					
	Frequency	•			•		
VISUAL TESTS	EV and EVSE visual tests	•					
FUNCTIONAL	Diagnostic test (EVSE)				•		
	Diagnostic test (Mode 2 EV cable)				•		
	CP simulation		•	•	•		
	PP simulation		•	•	•		
	Input error simulation				•		
	CP short / PE open / Diode short		•/•/•	• / - / -	•/•/•		
	Load test		13 A/phase			32 A/phase	
	Monitoring					•	
APPLICATION	Mode 2 EVSE tesing		•*	•*	•	•*	
	Mode 3 EVSE testing		•	•	•	•*	
	Mode 3 cables testing	•			•		•
	EV testing	•				•*	
CONNECTIVITY	Communication Port USB	•					
	Remotely controled via Android App				•		
	Remotely controled via Metrel tester				•		
	Built-in Bluetooth	•			•		
	Android Application	•			•		
PC SW	MESM	•	•	•	•		
ANDROID APP	aMESM	•					
	eMobility				•		* Limited

Special Installations Testing, Maintenance, Troubleshooting, Airports, Railway, Industry Ground Power Units, Sub-systems, Z impedance, Step/Contact, ELR, dR 300 A...



GENERAL FEATURES

- Hi precision 4-wire 300 A Z Line and Z Loop impedance tester;
- Hi range impedance measurements in 800 V / 16 ... 420 Hz AC networks;
- Hi current dR 300 A 4-wire partial voltage drop and current path resistance measurements;
- Earth Leakage Relay (ELR) testing;
- Ground fault analysis with Contact, Touch and Step Voltage;
- One-Clamp hi current grounding method with clamps (Flex & Iron);
- DC source & line resistance measurements in 3 ... 260 V DC networks;
- •• Bluetooth communication with Metrel's electrical safety testers;
- IP protection: IP65 (closed), IP54 (opened);
- Troubleshoot installation or appliances with leakage current tests
- Diagnose issues based on power and harmonic parameters
- Measure safely with remote wireless clamp
- Up to CAT IV 600 V (3000 m) safety category.

ADVANTAGES

- Earth Leakage Relay (ELR) Trip-out Testing Time and Current;
- Supported ELR types AC, A, B;
- Floating voltmeter for partial contact results;
- Selectable test load (16.6 % to 100 %);
- Improved thermal performance;
- Accessible inputs/outputs for connection of safety testers;
- Portable battery (Li-ion) or mains powered test

instrument;

- Automated 3-phase system testing;
- Remote controlled with supported Metrel safety testers or aMESM.

- Automatic trip-out protection evaluation in case of faults in transformers, generators, turbines, contactors, distribution boards and switch yards whenever energetic loads and sources of protection exceed 200 A.
- Power transformer and motor winding measurement.
- Live Power Transformer Hi Precision 4-wire 300 A Z Line / Loop Impedance Testing.
- Partial Voltage Drops and Partial Clamp Current's Path Resistance testing.
- Impedance testing of airport's Ground Power Units (GPU), railway systems.
- High accuracy battery resistance testing.
- DC Networks' and Power Sources' Line and Loop Resistance testing.
- Testing the integrity of Grounding systems and Lightning systems with High Current grounding method flex & iron One-Clamp method.
- Earth Leakage Relay (ELR/MRCD) testing.
- High current injection ground fault simulation.
- Automated testing of 3-phase systems.



FEATURES	Description	MI 3144 Euro Z 800V	MI 3143 Euro Z 440V	A 1722 PRCD adapter	A 1507 3-phase switch adapter	MD 9273 Leakage / Power Clamp
LECTRICAL	Zline mOhm high precision L-L, L-N, Ipsc - 4 wire	•	•			
NSTALLATION SAFETY	Zloop mOhm high precision L-PE, Ipfc - 4 wire	•	•			
	ΔR high current - 4 wire	•	•			
	R selective high current - 4 wire	•				
	DC source & Line Resistance	•				
	Earth Potential	•	•			
	ELR Test	•				
	AC Current	•				•
	Voltage	•	•			•
	Frequency	•				•
UNCTIONAL	Automated 3-phase system testing				•	
	Single phase PRCDs support			•		
	Threephase PRCDs support			•		
	Probe test			•		
	Power (S, Q, P, Cos phi, phi)					•
	128 Hz notch filter					•
	Harmonics and THD					•
	Loss analysis					•
ONNECTIVITY	Communication Port USB					
	Remotely controled via Android App	•	•			
	Remotely controled via Metrel tester	•	•		•	•
	Built-in Bluetooth	•	•		•	•
	Android Application	•	•			
	Communication Port RS232 - PS/2	•	•			
C SW/	MESM	•	•	•	•	•
NDROID APP	aMESM	•	•			

Special Installations Testing, Maintenance, Troubleshooting & Integrated IT Systems Z Line impedance, RCD, RCM, ELM, IMD, Earth...



GENERAL FEATURES

- AUTOSEQUENCE automatic tests, worst case evaluated, human error factor minimized;
- Automatic evaluation of safety for Medical Locations, Integrated IT systems and Installations on Vehicles, Fuse characteristics, supported IMD, ELM, RCM devices, adjusted limits and tested results combined together and evaluated simply as PASS / FAIL:
- Insulation and Earth Bonding Continuity for industrial environment and Special installations and Locations;
- Earth / Ground Resistance / Soil Resistivity in-line, triangle or mirror connection for close overlapped funnels on earthing systems, urban environment, also for industrial and noisy environment;
- Report Creator with powerful two way communication PC SW Tool EuroLink PRO.

ADVANTAGES

- Test of IMD, ELM and RCM devices with ISFL pretest and Voltage balance evaluation;
- Zloop L-N and L-L impedances at the entry and at the end of circuits, comparison of both results and dU calculation in %;
- Earth Bond testing with minimum 200 mA, 2 A, 10 A, both polarities, Inductive mode supported;
- Insulation testing through Switchboard, at Circuits, Insulation of Walls and Floors, Antistatic Floors testing;
- **PI and DAR** factor Insulation testing on cables, transformers, motors;

- Overvoltage varistors and Surge arresters testing with up to 2.5 kV voltage ramp;
- TRMS Clamp-on Leakage Current testing;
- Lightning systems and PE Conductive loops testing with Two Clamps method;
- 2-wire, 3-wire, 4-wire, 1 clamp, 2 clamps **Earth /** Ground resistance testing.

- Medical Sites and Specific Medical Units, Surgery Rooms, Ambulance Vehicles and Emergency Cars, Helicopters, Boats.
- Mobile Video / Audio / Concert Halls / Fair playground, Satellite / Video Broadcast Vehicles.
- Military and Police Portable Stations and Units, Vehicles, Helicopters, Airports, Mobile Units, Mobile Restaurant Units.
- Racing Team Mobile Units, Restaurant Units.
- Fire Brigade Engines and Vehicles, Fire Boats, Emergency Vehicles and Cars.
- Generators of working Ships and Boats, Fishing Boats and Ships, Transport Ships, Tourist Cruisers Ships, Marina places, Mobile Units with Integrated IT Generators / Transformers / LV Electrical Installations.
- Gas stations, Pipes, Ground metal plates and covers, Oil tanks.
- Earth, Ground and Lightning protection Systems of Buildings and Industrial Halls, from single earthing points to complex systems.



FEATURES	Description	MD 9272 Leakage / Power Clamp	MI 3123 Earth / Clamp	MI 3122 Z Line-Loop / RCD	MI 3121 Insulation / Continuity	MI 3121H Insulation / Continuity	MI 3242 MicroOhm 2A	MI 3110 EurotestIM
AUTOSEQUENCES	Auto IT (U, ZI, Is, Im)							•
INSULATION	IMD insulation monitor							•
	50 V - 1 kV				•	•		
	250 V, 500 V				•	•		
	2,5 kV PI DAR					•		
LEAKAGE CURRENT	ISFL L1, L2 first Fault leakage							•
	Differential leakage current	•						
	Leakage current with clamp	•						
CONTINUITY	Current 200 mA				•	•	•	
EARTH BOND	Current 2 A, 4-wire						•	
ZLINE	Zline, Ipsc, ΔU% / FUSE tables			•				•
ZLOOP	Zloop, Ipfc / FUSE tables Zs(rcd)			•				
RCD	RCD t, Uc			AC / A				
	RCD I ramp, Uc							
	Auto							
EARTH	Earth 3W		•					
	Earth 2 Clamps		•					
	RO adapter		•					
VOLTAGE	Voltage TRMS, Frequency	•		•	•	•		•
	Phase SEQUENCE L1-L2-L3			•				•
OTHER	Power (S, Q, PF, THDU)	•						
	Harmonics (U, I)	•						
PC SW	PC SW		•	•	•	•	•	•
COMMUNICATION	RS232 and USB		•	•	•	•	•	•
PORTS								

Portable Appliances Safety Testing, CE Marking & Machines Electrical Safety & Switchboards Safety Earth bond, Insulation, Differential / Touch / Substitute Leakage...



GENERAL FEATURES

- AUTOSEQUENCE automatic testing programmable or standardized shortcuts of any kind of Machines, Switchboards, Controlgear, Portable Appliances, Fixed Appliances, IT equipment, IEC cords, portable RCD devices and extension leads;
- Automatic evaluation of safety with simple PASS / FAIL information but supported with all subresults for detailed report;
- 3-phase appliance testing;
- PATLink Android scanning of the QR codes, containing information of the previous results, the test status, and the previously used test sequence;
- Scan, test and print barcoding system, and PASS / FAIL barcode label printing make retesting quick and simple;
- Active polarity for P/RCD protected extension leads testing;
- Report Creator with powerful two way communication PC SW Tool PATLink PRO.

ADVANTAGES

- HV Withstanding dielectric test with programmable voltage ramp AC, 500 VA, up to 5.1 kV, fixed voltage levels 1 kV, 1,89 kV, 2.5 kV and limited power Flash tests on 1.5 kV / 3 kV;
- Earth bond / continuity resistance test with test currents 200 mA and powerful 10 A / 25 A;
- Insulation resistance, Touch leakage current and Substitute leakage current on inner and exposed isolated accessible conductive parts for class I /

class II appliances;

- Differential Leakage, Touch Leakage and Substitute Leakage test;
- Functional test and TRMS load currents testing;
- Innovative Active Polarity function for testing RCD / PRCD protected cords while voltage is applied to tested item;
- **Trend** function showing comparison of old and new test results on large graphic LCD display;
- Instrument can be powered from both mains supply and internal battery;
- Results can be read / written / sent via USB, Bluetooth, External Printer, Barcoding, QR Coding and RFID system.

- Type testing of Appliances, Machines and Switchgears / Controlgears after production in producer's R&D phases and Laboratories.
- CE marking and Routine testing after production.
- Testing of Power Tools, Extension Leads and Appliances on Construction sites.
- Testing of Appliances protected with RCDs (type AC, A, and B), portable PRCDs (type K, S).
- Service departments (after repair testing), Hire and Rental Industry (before hire and after return testing).
- Periodic testing of Portable Appliances for Hotels, Schools, Kindergardens, Public places, Restaurants, Kitchens, Shopping Centers, Stores, Fire Brigades, Military, Expo Centers, Concert Halls, Events.
- Testing of Hard-wired Appliances.



			MultiTesterXS	CE MultiTesterXA	OmegaEE XD NEW	OmegaGT XA	DeltaGT	GammaGT
ITOSEQUENCES		•/•/•/-/•	•/•/•/-/-	•/•/•/-/-	-/•/-/•/•	-/•/-/•/•/•	-/•/-/-/-/-	-/•/-/-/-
	AUTOSEQUENCE Programmable	•	•	•	•	•	•	•
	Auto VDE	•			•	•	•	•
	Auto CUSTOM	•	•	•	•	•	•	•
ITHSTANDING	Ramp test 100 5100 VAC (500 VA)	• **	•	•				
	Ramp test 500 6000 VDC		•	•				
		•/•/•/•/•	•/•/•/•/•	•/•/•/•/•	_/•/-/•	/•/-/-/•		
DNTINUITY	Current 200 mA	•	•	•	•	•	•	•
ARTH BOND	Current 4 A / 10 A / 25 A	•/•/•	•/•/•	• / • / •	- / • / •	- / • / •	- / - / -	- / - / -
SULATION	50 VDC / 100 VDC / 250 VDC / 500 VDC / 1000 VDC	•/•/•/•/•	•/•/•/•/•	•/•/•/•/•	- / - / • / • / -	- / - / • / • / -	- / - / • / • / -	-/-/•/•/-
EAKAGE CURRENT	Differential leakage current	•	•	•	•	•	•	
	Touch leakage current	•	•	•	•	•	•	
	PE leakage current	•	•	•	•	•		
	Substitute leakage current	•	•	•	•	•	•	•
	Leakage current measurement with optional clamp	•			•	•	•	
	Leakage current produced by a floating input, PE current				•	•		
	Leakage current produced by a floating input, Touch current				•	•		
	Equipment Leakage				•	•		
	Applied Part Leakage				 M (Only) 	 M (Only) 		
	Patient Leakage				 M (Only) 	 M (Only) 		
SCHARGE TIME	60 V (1 5 s)	•	•	•	 M (Only) 	 M (Only) 		
	120 V (1 5 s)	•	•	•				
ID IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	RCD t, Uc, RCD I ramp, Uc, Auto	AC / A / B / B+ / F			AC / A / B / B+ / F	AC / A / B / B+ / F	AC / A*	
	PRCD-S, PRCD-K	• ***			•	•	•	
	IC-CPD (EV RCD)				•			
	IC-CPD_PE Conductor (EV RCD)				•			
LINE	Zline, Ipsc, ΔU% / FUSE tables	•						
	MI 3143 / MI 3144 (Adapters)	•/•						
.00P	Zloop, lpfc / FUSE tables Zs(rcd)	•						
IREE PHASE	A 1322 Active 3-phase Adapter	Optional			Optional	Optional		
PPLIANCES	A 1422 Active 3-phase Adapter Plus	Optional			Optional	Optional		
DLTAGE	Voltage TRMS / Frequency	•/•	• / -	• / -			• / -	• / -
	Phase SEQUENCE L1-L2-L3	•	/	/			/	
	Voltage, SELV/PELV				•			
	EVSE Diagnostic test				•			
DLARITY	IEC lead test	•			•	•	•	•
	Active polarity	•			•	•		
THER	Safety modules		Optional					
	Functional test	•	•	•	•	•	•	
	EVSE (A 1632 eMobility Analyser)	Optional						
	Power	•	•	•	•	•	•	
	Barcode	Optional	Optional	Optional	Optional	Optional	Optional	Optional
	Printer	Optional	Optional	Optional	Optional	Optional	Optional	Optional
UETOOTH	Built in	•	•	•	•	•	•	орнона
	External (dongle)	-	· ·	·	-	-	-	•
ODULE								
SW	PC SW PATLink PRO Plus						•	•
	PC SW Metrel ES Manager	•	•	•	•	•	•	
OMMUNICATION	RS232 / USB / Ethernet Remote	•/•/•	•/•/•	•/•/•	• / • / -	• / • / -	• / • / -	• / • / -

* RCD t, only / ** 250 VA only / *** PRCD-S and S+ only

Medical equipment, medical systems, surgery room IT installation Maintenance & periodic testing, industrial testing, type testing, testing IT installations...





GENERAL FEATURES

- Patient leakage tests in all IEC 60601 configurations.
- Insulation measurements in all IEC 62353 configurations.
- Earth bond measurements with 200 mA, 10 A or 25 A.
- Measurement of leakage, THD and power for troubleshooting.
- Evaluation of results with PASS or FAIL regarding the limits in standards.
- Support for scanners and printers.
- Powerful online reporting system.
- 3-phase device support.
- Android applications aMESM, aPAT and PAT Link Android for easy data input, code scanning and report creation in the field.
- IMD, ELM and RCM tests.
- ISFL test and voltage balance evaluations.

ADVANTAGES

- The most complete IEC/EN 60601 tester on the market.
- Support for both medical and PAT standards in a single instrument.
- 10 universal configurable connections to measure applied parts, non-earthed parts or earthed parts.
- All possible configurations according to IEC/EN 60601 and IEC/EN 62353 standards.
- Full functionality without using a PC.
- Remote control from PC with graphical user interface.
- Automatic workflow with Auto Sequences[®].

- Automatically generated Auto Sequences[®] based on connection configuration.
- One-button test for the safety of IT installations.
- Custom visual and functional tests.

- Safety of medical equipment in type, production, periodic or after-repair testing.
- Periodic and after-repair testing of portable appliances.
- Troubleshooting of medical equipment and portable appliances.



FEATURES	Description	MI 6601	MI 3365 M	MI 3360 M	MI 3110
		MediTest NEW	OmegaEE XD NEW	OmegaGT XA	EurotestIM
JTO SEQUENCES®	Predefined IEC/EN 60601 Predefined IEC/EN 62353	•			
	Predefined IEC/EN 62353 Programmable	•	•	•	
	Exclude steps Predefined IEC/EN 60364-4-41	•			
	Predefined IEC/EN 60364-4-41				•
ARTH BOND	Custom inspections	•	•	•	
	Current 200 mA Current 10 A	•	•	•	
	Current 25 A	•	•	•	
SULATION	250 V 500 V	•	•	•	
AKAGE CURRENT	Differential method	•	•	•	
SIC	PE method	•	•	•	
JIC	louch leakage	•	•	•	
	Substiture method	•	•	•	
	Optional clamp	•	•	•	
AKAGE CURRENT	Leaks and power diagnostic Applied parts alternative method Applied parts direct method	•	•	•	
/EN 62353	Applied parts direct method	•	•	•	
•	Equipment alternative method	•	•	•	
	Equipment differential method	•	•	•	
	Touch leakage	•	•	•	
AKAGE CURRENT	Applied parts direct method Equipment alternative method Equipment differential method Equipment differential method Touch leakage Patient leakage general Patient leakage special Total patient leakage general Total patient leakage special Touch leakage noint to noint	•			
C/EN 60601	Patient leakage special Total natient leakage general	•	•	Optional	
	Total patient leakage special	•		•	
	Touch leakage	•	•	Optional	
Ds	louch leakage point to point	•	•	•	
50	PRCD-S. PRCD-K		•	•	
	IC-CPD (EV RCD)		•		
CVCTENA	Touch leakage point to point RCD t, Uc, RCD I ramp, Uc, Auto PRCD-S, PRCD-K IC-CPD (EV RCD) IC-CPD PE Conductor (EV RCD)		•		
SYSTEM	Voltage monitor				•
	Line impedance				•
	Line impedance IMD/ELM/RCM testing				•
LTAGE	Mains Point-to-point	•	•	•	•
	Point-to-point Touch	•			
	EV diagnostic test		•		
PHASE	Phase sequence		•	•	•
CABLES	3-phase adapter supported IEC cable test	•	•	•	
	Active polarity	•	•	•	
HER	Power	•	•	•	
	Barcode/QR code scanner Printer	•	•	•	
MUNICATION	Bluetooth	•	•	•	
	Bluetooth USB/RS232	•	•	•	•
	Lthornot	•	•	•	
	Remote control Command line	•	•	•	
FTWARE	Metrel ES Manager		•	•	
	Remote control command line Remote control GUI Metrel ES Manager Metrel Medical ES Manager	•			
	EUROLINK				•
	aMESM (Android)		•	•	

Power and Voltage Quality & Consumption and Disturbances Power, Harmonics, THD, TID, TDD, Phase diagram, Unbalance, Flicker, Transient, Waveform...



GENERAL FEATURES

- Automatic Voltage and Power Quality Analysis according to EN 50160 with PASS / FAIL limit evaluation, including flickers and harmonics;
- IEEE 519 2022 Standard for Harmonic Control in Electric Power systems report creation;
- Energy Demand report creation;
- Compliance with power quality standard IEC 61000-4-30 Class A/S;
- Predefined recorder profile for EN 50160 survey;
- Troubleshooting and Maintenance Tool to discover voltage sags and swells, resonant states, high neutral conductor currents in 3-phase systems, asymmetry, transients;
- Designing Tool of filtering systems, power correction equipment, over voltage protection and UPS systems;
- Power Quality Negotiating background Tool;
- Download, view and analyse with PowerView
 PC SW platform that contains a package of functionalities needed for evaluation of power quality phenomena and creation of complex reports.

ADVANTAGES

- Voltage TRMS, peak, crest factor (4-channel), 0 ... 1000 Vrms;
- Current TRMS, peak, crest factor (4-channel),

automatic clamp recognition;

- **Power** (fundamental, non fundamental, combined, active, reactive, apparent), Power factor, cos fi, Unbalance;
- Power harmonics;
- Harmonics Pollution;
- Energy (fundamental, non fundamental, combined, active, reactive, apparent, generated, consumed);
- Harmonic analysis up to 50th harmonic, THD, TID, TDD measurement, K-Factor;
- VFD measurement;
- 50/60 Hz, 400 Hz;
- Power measurement: IEEE 1459 / Classic (Vector, Arithmetic);
- Flicker measurement;
- Waveform displaying and Transient snapshotting;
- Fast logging and Inrush Current recording;
- Fast transient recording;
- Signalling;
- Temperature measurement;
- Faster troubleshooting due to on-screen displaying of trends and captured events;
- Voltage events and user defined alarms capture:
- GPS time synchronization;
- Internal memory allows recording over one year period exchangeable SD card;
- Instrument, or a group of them, can be remotely controlled and programmed via Ethernet or GPRS/Wi-Fi modem.



- Power Factor Compensation measurements, Power Quality, Maintenance, Filters, Inrush current measurement.
- Power quality assessment and troubleshooting in low and middle voltage electrical systems.
- Energy assessment to quantify the before and after installation improvements in energy consumption in order to justify energy saving devices,
- Checking power correction equipment performance.
- Long-term analysis, to uncover hard-to-find or intermittent issues.
- Predictive maintenance, to detect and prevent power quality issues before they cause downtime.
- Load studies, to verify electrical system capacity before adding loads.
- Inrush current, unbalance/asymmetry recording to optimize systems efficiency.
- Fast transient detections.
- Electrical Safety in Public Areas.

FEATURES	Description	MI 2893 Power Master XT	MI 2892 Power Master	MI 2885 Master Q4	MI 2884 Energy Master XA	MI 2883 Energy Master
LASS	IEC 61000-4-30 Class A / Class S	Class A 0.1% (Independent certificate)	Class A 0.1% (Independent certificate)	Class S (0.1%) (Independent certificate)	Class S (0.2%)	Class S (0.2%)
INPUTS	Number of current measuring inputs	4	4	4	4	4
	Number of voltage measuring inputs	4	4	4	3	3
PERIODICS	TRMS Voltage measurement (Min., Max., Avg.)	•	•	•	•	•
	TRMS Current measurement (Min., Max., Avg.)	•	•	•	•	•
	Current in neutral conductor	•	•	•	•	•
	Power Factor and cos fi	•	•	•	•	•
	Power measurement (W, VA, VAr)	•	•	•	•	•
	Energy measurement	•	•	•	•	•
	THD and harmonics analysis	•	•	•	•	•
	Frequency measurement	•	•	•	•	•
	Flicker measurement	•	•	•	•	•
	Voltage events (sags, swells, interruptions)	•	•	•	•	•
	Unbalance	•	•	•	•	•
	EN 50160 Analysis / IEEE 519 Analysis	• / •	• / •	• / •	• / •	• / •
ON LINE	Scope function	•	•	•	•	•
	Phase diagram	•	•	•	•	•
	Harmonics measurement	•	•	•	•	•
SPECIAL TOOLS	Transients measurement	• (>1 Msamples/sec)	 (> 49 ksamples/sec) 	 (> 49 ksamples/sec) 	• (> 30 ksamples/sec	:)
	Waveform recording	•	•	•	•	
	Inrush currents	•	•	•	•	
	Electricity meter accuracy check		•	•		
	Variable Frequency Drives	•	•	•		
OTHER	Interharmonics analysis	•	•	•	•	•
	Connection check	•	•	•	•	•
	Smart clamps auto ranging	•	•	•	•	•
	Signalling	•	•	•	•	•
	Temperature measurement	•	•	Optional	Optional	Optional
PC SW	PC SW PowerView3 (free of charge)	•	•	•	•	•
	EN 50160 / IEEE 519 /Energy consumption report	•/•/•	•/•/•	•/•/•	•/•/•	•/•/•
	Regional reporting (optional) /Export of data via custom filtering	• / •	• / •	• / •	• / •	• / •
COMMUNICATION	MicroSD memory card	•	•	•	•	•
PORTS	RS232	GPS receiver only	GPS receiver/ Scanning photo head	GPS receiver/ I Scanning photo head		
	USB	•	•	•	•	•
	Ethernet / Intranet	• / •	• / •	• / •		
	GPS time synchronisation	•	•	•		
	Remote instruments control (4G/WiFi)	Optional	Optional	Optional		

HV Safety and Quality in Industrial Systems & Power Generation & Distribution Systems & Equipotential Bonding, Insulation Analysis, Step / Contact, Transformer testing...





GENERAL FEATURES

- Equipotential Bonding and Connectivity Testing with MicroOhm meter is just what needed to show reliable and stable results;
- HV Insulation Analysis with high EMC immunity, three wire connection with Guarded test leads in the set. Powerful generator with fast charging and discharging of Capacitive loads;
- Voltage Funnel during Fault Simulation in case of ground fault or lightning strike around objects, analysing with Step Voltage and Contact Voltage measuring, Earth / Ground Resistance and Soil Resistivity measuring with Step / Contact System;
- Transformer measurements: The operation is straightforward and clear to enable the user to operate the instrument without the need for special training;
- Report Creator with powerful PC SW Tool HVLink PRO or MESM.

ADVANTAGES

- Equipotential Bonding with 4 wire MicroOhm meter with 2A, 10A or 100A battery operated generator with results in fine resolution up to 1 nanoOhm;
- HV Insulation Analysis up to 10 kV, 3 wire connection with +, - and Guard, with PI, DAR, DD, Ramp test, Withstanding programmable procedure and Step Voltage. Graphical presentation of results R(t);
- Smallest Step / Contact Voltage System with wireless synchronized Voltmeters all in one solution, with powerful generator of up to 55 A, eliminating earth current noise even in

low power operating mode. It is extremely **safe operating on 50 V** only which is important for testing in public area surrounding;

• Single and 3- phase transformer winding resistance and turn ratio measurements.

- Equipotential Bonding and Connectivity of bigger crossection conductors, bars and metal stripes, connected in paralel.
- Testing of Automatic Disconnection Ability in case of Fault in Power Transformer, Fuse characteristics evaluation with 4-wire 300 A High-Current Testing.
- Insulation Characteristics of Charging and Discharging, Influence of temperature, dirt, humidity, mechanical and electrical stresses, highenergy radiation, Testing on Capacitive loads, Long Cables and Transformers.
- Insulation testing on separated systems of gas stations, pipes, ground metal plates and covers of oil tanks.
- Overvoltage and Surge Protection Periodical Testing.
- Earth and Ground systems, Soil resistivity, Lightning protection of Power Generators, Industrial Power Systems, Power Substations.
- Ground Networks Analysing of Antenna Towers, HV Power Distribution towers, Industrial Platforms, Power Transformers, Generators, PV systems etc, research on Earthing and Spreading of Voltage Funnels.
- Transformer winding resistance and turn ratio measurements.



Construction Sites Selection Guide

FEATURES	Description	MI 3252 MicroOhm 100A	MI 3250 MicroOhm 10A	MI 3210 TeraOhmXA 10 kV	MI 3205 TeraOhmXA 5 kV	MI 3201 TeraOhm 5 kV Plus	MI 3202 GigaOhm 5 kV	MI 3290 Earth Analyser	MI 3288 Earth Insulation Tester	MI 3280 DT Analyser	MI 3281 WR Analyser	MI 3295 Step Contact Voltage
EARTH BOND /	Test current range	100 A	10 A					200 mA	200 mA	1 A	20 A	
VINDING	Resolution	1 nΩ	0.1 μΩ					10 mΩ	1mΩ	0.1 mΩ	0.1 μΩ	
RESISTANCE	Single / Continuous mode	•	•					•	•			
	Inductive mode		•					•	•	•	•	
RANSFORMER	Winding resistance 1 ph/ 3 ph									• / •	• / •	
ESTING	Turn ratio 1 ph/ 3 ph									• / •		
	Tap changer control									,	•	
	Demagnetization										•	
NSULATION	Custom test shortcut			•				•				
NALYSING	Test voltage range			50 Vpc 10 kVpc	50 Vpc 5 kVpc	250 Vpr 5 kVpr	250 Vpc 5 kVpc		50 Vpc 2.5 kVpc			
	Insulation resistance measuring range			20 ΤΩ	15 ΤΩ	10 ΤΩ	1ΤΩ		100 GΩ	·		
	Calculation of DD, DAR, PI, R(t)			•	•	•			•			
	Ramp voltage test			•	•	•			•			
	Step voltage test			•	•	•						
	Bar graph			•	•	•	•		•			
	Leakage current			•	•	•			•			
	Automatic discharge			•	•	•	•		•			
	5 Test current up to 55 A				-				-			•
	Autonomous step voltage meter							•				•
	Step & contact voltage							•	•			•
	Earth resistance 2W / 3W / 4W							•/•/•	•/•/•			- / - / •
	Specific earth resistance Wenner /							•/•	•/•			•/-
	Schlumberger							• / •	• / •			• / =
	Multi frequency method							•	•			
	High frequency method							•	_			
	Selective 1/4 clamp method							•/•	• / -			
	Stakeless 2 clamp method							•	•			
/OLTAGE	Voltage 600 Vpc / 1000 Vpc			• / -	• / -	• / -	• / -	-	• / •			
OLIAGE	Voltage 750 Vac			• / -	• / -	• / -	• / -		•			
THER	Robust AC current rejection 4 mA			•	•				-			
THER	Noise immunity filter	•	•	•	•	•	•	•	•			•
	PASS / FAIL evaluation	•	•	•	•	•	•	•	•	•	•	•
		-	•	-	-	-	-	-	-	-	•	-
	Temperature compensation	1			1.1.1	NEMALI	NEMALI	1.1.1	1.1.1	1.1.1	•	
	Dual powered	Lead	NIMH	Lead / Li-Ion	Li-lon •	NIMH •	NiMH	Li-lon •	Li-lon	Li-lon •		
	PC SW		•	•							•	•
COMMUNICATION PORTS	RS232 / USB / BT	•/•/-	• / • / -	•/•/•	•/•/•	• / • / -		-/•/•	-/•/•	-/•/•	-/•/•	•/•/-

General testing up to high level industrial testing, electronic fault finding, field servicing & heavy TRMS AC, DC voltage / current; Capacitance; Resistance; Diode test...



GENERAL FEATURES

- **PC Link** software enables downloading test results to the computer;
- Lead alert indicates incorrect lead connection;
- **Temperature measurement** measures T1, T2 and T1 + T2 temperature in Celsius and in Fahrenheit;
- MAX/MIN/HOLD mode, displays maximum, minimum or average measured value;
- Auto Hold automatically feature freezes the stable result for later view;
- Non-contact and probe contact electric field detection;
- Insulation resistance measurement with up to 1000 V test voltage;
- Continuity measurement with 200 mA;
- PI/DAR measurement;
- 4-20mA DC current loop test;

ADVANTAGES

- Relative zero mode function for comparing the difference between signals or removing background noise;
- 100 kHz Voltage Bandwidth;
- Large 2-line 500.000 counts LCD display;
- Automatic detection of AC voltage, DC voltage or resistance;
- Frequency measurement up to 1 MHz.

- High, Mid and Low level industrial testing.
- High, Mid and Low level electronic fault finding.
 HVAC (heating, ventilation and air conditioning) troubleshooting.
- Demanding measurement tasks in the laboratories.
- Everyday repair and maintenance practice.
- Heavy duty electrical testing.
- Field servicing.
- Automotive industry.
- Hobby work.
- Working in small enclosures.
- General purpose.



duty electrical testing Selection Guide

FEATURES	Description	MD 9070	MD 9060	MD 9055	MD 9050	MD 9040	MD 9016	MD 9010
AEASURING METHOD	True RMS	•	•	•	•	•		
AC - MEASUREMENTS	Current		0.1 uA 10 A	0.1 uA 10 A	0.1 uA 10 A	0.1 uA 10 A	0.1 uA 10 A	0.1 uA 2 mA
	Voltage	1 mV 1000 V	0.01 mV 999.9 V	0.01 mV 1000 V	0.01 mV 999.9 V	0.01 mV 999.9 V	0.01 mV 999.9 V	1 mV 600 V
	Frequency	•	•	•	•	•	•	•
	Frequency of digital signals		•	•	•	•		
	100 kHz Voltage bandwidth		•					
	Duty cycle (%)		•	•				
C - MEASUREMENTS	Current		0.1 uA 10 A	0.1 uA 10 A	0.1 uA 10 A	0.1 uA 10 A	0.1 uA 10 A	0.1 uA 2 mA
	Voltage	1 mV 1000 V	0.1 mV 999.9 V	0.1 mV 1000 V	0.01 mV 999.9 V	0.01 mV 999.9 V	0.01 mV 999.9 V	1 mV 600 V
THER	Resistance	•	•	•	•	•	•	•
IEASUREMENTS	Acoustic continuity	•	•	•	•	•	•	•
	Capacitance		•	•	•	•	•	•
	Diode	•	•	•	•	•	•	•
	Temperature T1 / T1 &T2		•/•	•	•/•		•/ -	
	Earth continuity test	•						
	Insulation resistance	•						
	PI / DAR	•						
	EF (Electric field detection)			•	•		•	•
	Conductance		•	•	•			
	VFD (Variable frequency drive)	•	•	•				
THER	Autocheck (VAC-DC; Ω)			•	•			
UNCTIONS	Data hold	•	•	•	•	•	•	
	MAX	•	•	•	•			
	MIN	•	•	•	•			
	AVG (recording)		•	•	•			
	Auto ranging	•	•	•	•	•	•	•
	Relative zero mode		•	•	•	•	•	
	Analogue bargraph	•	•	•	•	•	•	
	Lead alert		•	•	•	•		
	Count	6000	50.000 / 500.000	60.000	6000 / 9999	6000 / 9999	6000	6000
ECHNICAL DATA	Backlight	•	•	•	•			
	IP protection	40	54	40	54	54	40	40
OMMUNICATION	PC Link		•		•	•	•	
VERVOLTAGE	CAT IV / 1000 V		•		•	•		
ATEGORY	CAT IV / 600 V	•		•				
	CAT IV / 300 V						•	
	CAT III / 1000 V	•						
	CAT III / 600 V						•	
	CAT III / 300 V							•

General testing up to high level industrial testing, electronic fault finding, field servicing & heavy TRMS AC, DC current, Leakage current, Single/3-Phase Power, Voltage...



ENERAL FEATURES

- PC Link software enables downloading test results to the computer;
- Different Jaw size to cover different applications;
- **Shielded jaws** allowing the clamp meter to be used in the noisiest environments;
- MAX/MIN/HOLD mode, displays maximum, minimum or average measured value;
- Power and power factor measurements;
- Non contact voltage detection;
- Non contact phase sequence detection;
- Harmonic analysis;
- Kilo-Watt-Hour recording function (with memory recall).

ADVANTAGES

- Intelligent loss analysis: complex algorithms detect loss and allow determining possible reasons for current loss:
- Bluetooth connection to Metrel testers;
- 1500 V DC range with CAT III safety for work on solar plants;
- Accurate: readings of AC current with an accuracy of 0.8 % and a base resolution of 0.01 mA and voltage with an accuracy of 0.5 % and a base resolution of 0.1 V;
- Lo-Z: AutoCheck[™] mode provides low (ramp-up) input impedance to drain ghost voltages;
- High current, up to 2000 A DC & AC clamp on measurement;
- **In-rush**, fast 30 ms Crest-MAX mode to capture in-rush currents.



APPLICATIONS	 -
 Load and leakage current measurement. RCD fault finding. UPS system testing. 	
 Folar and wind now or system testing 	

FEATURES

- Solar and wind power system testing.High powered 3-phase machinery testing.
- High current electrical testing.
- Utility scale battery system testing.
- High level industrial testing.
- Power system checking.
- System maintenance.
- Process engineering.
- Working in small enclosures.
- General purpose.

MEASURING METHOD	True RMS
AC - MEASUREMENTS	Current
	Voltage
	Frequency
DC - MEASUREMENTS	Current
	Voltage
POWER	Active
MEASUREMENTS	Reactive
	Apparent
	Power factor
	Crest factor
	kWHr recording
	3-phase power
OTHER	Resistance
MEASUREMENTS	Acoustic continuity
	Capacitance
	Diode
	Temperature
	EF (Electric field detection)
	Phase (-180° +180°)
	Harmonics
	THD
	In-rush
	VFD (Variable frequency drive)
	Lo-Z (low input impedance)
	Leakage current
OTHER	Autocheck [®] V-Ω
FUNCTIONS	Data hold
	MAX hold
	MAX/MIN/AVG
	Peak value
	Auto ranging
	Relative zero mode
	Counts
TECHNICAL DATA	Backlight
	Jaw opening
COMMUNICATION	PC Link
OVERVOLTAGE	CAT IV / 1000 V
CATEGORY	CAT IV / 600 V
	CAT IV / 300 V
	CAT III / 1500 VDC
	CAT III / 1000 V
	CAT III / 600 V

Description

duty electrical testing Selection Guide

MD 9273	MD 9272	MD 9260	MD 9250	MD 9235	MD 9231	MD 9226	MD 9225	MD 9210	FEATURES	Description		MD 1160	I-LCD	MD 1060-LED
2														þ
•	•	•	•	•	•	•	•		AC - MEASUREMENTS	Voltage range		12 V 6	90 V	12 V 690 V
10 u.A 100 A	10 uA 100 A	0.1 A 2000 A	0.1 A 2000 A	10 mA 600 A	10 mA 1000 A	10 mA 600.0 A	0.1 A 400 A	10 mA 600 A		Frequency		16 Hz	400 Hz	16 Hz 400 H
0.01 V 600 V	0.01 V 600 V	1 mV 999.9 V	1 mV 999.9 V	0.1 V 600 V	0.1 V 1000 V	0.1 V 600.0 V	1 mV 600 V	1mV600V	DC - MEASUREMENTS	Voltage range		12 V 6	90 V	12 V 690 V
•	•	•	•	•	•	•	•	•	OTHER	TRMS		•		•
		0.1 A 2000 A	0.1 A 2000 A		10 mA 1000 A	10 mA 600.0 A	0.1 A 400 A		MEASUREMENTS	Acoustic continu	uity	•		•
D.01 V 600 V	0.01 V 600 V	1 mV 1500 V	1 mV 999.9 V	0.1 V 600 V	0.1 V 1000 V	0.1 V 600.0 V	0.1 mV 600 V	0.1 mV 600 V		indication				
•	•			•						Continuity test		0 500	kΩ	0 500 k Ω
•	•			•						Single-Pole Pha	se	•		•
•	•			•						Phase rotation		•		•
•	•			•						Max. test currer	it	< 3,5 m/	A @ 690 V	< 3,5 mA @ 69
•	•									Automatic rang		•		•
				•						selection				
				•						Reaction time		< 0,1 s		< 0,1 s
		•	•	•	•	•	•	•	OTHER	Automatic AC/D)C	•		•
		•		•	•	•	•	•	FUNCTIONS	recognition				
		•	•	•	•	•	•			Automatic ON/	1FF	•		•
		•			•	•	•	•	TECHNICAL	LED torch lamp	511	•		•
		•	•		•	•	•	•	INFORMATION	Display		LCD & LI	=n	LED only
		•	•		•	•	•			IP protection		64		64
	•	•	•		•	•				Operating temp	erature		°C < 85%	-15 55 °C < 8
•	•									operating temp	crucure			relative humid
•	•									Dimension				240 x 65 x 19 r
•	•									Weight		180 g		170 g
•							•		OVERVOLTAGE	CAT IV / 600 V		•		•
•		•	•		•	•			CATEGORY	CAT III / 1000 V				
			•						CATEGORY	CAT III / 1000 V				
•	•													
		• *	• *	•			•		FEATURES	Description	MD 126		4D 116	MD 106
•	•	•	•	•	•	•	•	•		200000		-		
•	•	•	•		•	•	•	•			-		-	(m)
•	•												1	
•	•				•	•							1	
•	•	•	•	•	•	•	•	•						-
		•	•		•	•	•	•						
4000	4000	6000	6000	6000	6000	6000	4000	4000			- 46		-	-
•	•	•	•	•	•	•	•				- W		1	19
28 mm	31 mm	55 mm	55 mm	26 mm	51 mm	35 mm	26 mm	26 mm	DETECTION RANGE	Voltage	100 V	1000 V 1	2 V 1000	V 90 V 100
		•	•	•						Frequency	50 60		10 400 Hz	
		•	•							Phase sequence	•			
					•	•			INDICATION	Optical	•			•
•	•		•	•			•	•		Acoustical	•			•
		•								Vibrating		•		
		•			•	•			TECHNICAL DATA	IP protection	67	6	55	65
										Overvoltage cat.		10001/ 0	AT N/ / 100	0 V CAT IV / 10

Building and facility management, electrical and other installations troubleshooting, mechanical Temperature, temperature difference...



ENERAL FEATURES

- High thermal resolution 80 x 80 pxl or 120 x 150 pxl;
- Temperature range -20 ... 350°C for cameras and -20
- ... 260°C for multimeter; • Good sensitivity of **100 mK**;
- Accuracy 2°C or 2%;
- Manual, automatic or fixed focus;
- Manual, automatic of fixed foc
 Small focal length of 7.5 mm;
- Small rocal length of **7.5 mm**;
- Emissivity range 0.01 1.00;
- Automatic, locked or manual temperature span.

ADVANTAGES

- High quality French thermal sensor;
- Sturdy, high IP, 2 m drop test;
- Very fast refresh rate 50 Hz;
- Set includes bag or case for protection and easy carrying;
- Powerful PC software for transfer, editing, analysis of the images and report creation;
- SB and HDMI connectivity;
- Thermal and visible light video with audio commentary.

- Troubleshooting electrical installations (switchboards, busbars, contacts, etc.);
- Troubleshooting electrical equipment (motors, transformers, etc);
- Troubleshooting mechanical issues (gears, bearings, etc.);
- · Inspecting and troubleshooting electrical vehicles;
- Solar farm inspection;
- Building and facility maintenance;
- Field service;
- Energy loss analysis;
- Troubleshooting other installations (windows, pipes, carpentry, etc.).



and electrical inspections Selection Guide

FEATURES	Description	MD 9930 Thermal camera	MD 9880 TRMS thermal multimeter
FEATURES	IR sensor resolution	160 x 120 pxl	80 x 81 pxl
	Temperature range	-20 350°C	-20 260°C
	Thermal sensitivity/NETD	0.1°C @ 30°C / 100 mK	0.1°C @ 30°C / 100 mK
	Thermal accuracy	±2°C or ±2 %	±3°C or ±3.0 %
	Field of vision	25° x 19°	21° x 21°
	Spectral range	8 14 µm	8 14 µm
	Emmisivity range	0.01 1.0	0.01 1.0
	Frame rate	50 Hz	50 HZ
	Focal length	9 mm	7.5 mm
	Spatial resolution	2.78 mrad	4.53 mrad
	Level and span	Auto and manual	Auto
	Min focused distance	0.5m	0.5m
	Focus	Manual	Fixed
	Visible light camera	•	
	Fusion view	•	
	Display resolution	240 x 320 pxl	240 x 320 pxl
	Thermal video	•	
GENERAL	Data storage	Internal 100 MB + SD card up to 32 GB	
	Battery	Li-lon, up to 4h	Li-lon, up to 6h
	Multimeter		•



GENERAL FEATURES*

- Unified user interface with the new generation of
- Metrel's instruments same view same meaning;
 Multilevel test structure editor: the installation structure can be created in advance on the PC and then simply uploaded to your tester;
- Measurement editor: enables viewing and editing of measurement results;
- Auto Sequence[®] editor: application for easy and efficient preparation of Auto Sequence[®]s or custom tests:
- Upload/download of Auto Sequence®s and work structures to/from the instrument from/to the PC and/or Android smartphone/tablet;
- Report creator: enables automatic generation of professional test reports which include visual inspection of tested object and test results in tabular form;
- · Licence upgrading tool;
- Multilingual support.

ADVANTAGES*

- Export of test results to excel or .xml format for analysis and integration to 3rd party SW;
- Possibility to upgrade FW on devices;
 Symphonize licenses between the measurements.
- Synchronize licenses between the measuring device and the PC;
- Creation of Auto Sequence[®]s and visual inspections;
- Printing of multilingual professional reports or basic reports according to local regulations;

- Automatic fill-out of reports with measurement data;
- Integration to other 3rd party SW via Metrel SDK library;
- Black-box protocol for online communication and starting tests remotely on new generation of Metrel's instruments;
- **Remore control**: via GPRS communication remote handling of the power quality instruments;
- Complete database of tested installations in one location;
- Easy data entering;
- Projects can be stored to your Dropbox account;
- Sending data to the main office before leaving the test site;
- · Overview of testing parameters;
- Adding text, picture, video or voice records to test results;
- Use of smartphone's barcode or QR code scanner for quicker data entry;
- View the results of the I/V measurement in graphical or numerical form;
- Use of smartphone's camera for QR and barcode scanning;
- Use of smartphone's virtual keyboard;
- Built-in risk assessment tool to provide correct retest periods in accordance with COP version 4;
- "Drag and drop": downloaded data can be easily organized into multiple sites and sub-site locations;
- Data filtering: data in a structure can be grouped by quantity or by phase;
- GPS synchronization: simultaneous measurement on different network points by using 2 or more synchronized instruments;
- On-line monitoring: when instrument is connected

with PC, real-time observing of signals and parameters is possible via PowerView3 while instrument is measuring / recording in the background;

• SW updating.

APPLICATIONS*

- · Upload/download measurement results;
- Create, view, analyse and edit structures / Auto Sequence[®]s.
- Professional report creation and printing;
- Integration to 3rd party SW via SDK, blackbox protocol, Excel or XML.

*Note: Presented features, functionalities and other information on this page represent a compound list of all software/Android app's capabilities and not capabilities of each separate software/Android app. Consult user manuals of each specific software/ Android app for detailed information about supported features and functionalities.



multimeter Windows Software and Android Apps Selection Guide

GROUP	Instrument/Software	SW 1201 MESM	SW 1203 Metrel SDK**	SW 1402 MMESM NEW			SW 0101 EuroLink PRO			Black Box	aMESM	SW 1303 aPAT Android	EuroLinkP\	/ PATLink	SW 1307 EuroLink Android	aMIRA	Data) SW 1311 Data Rec.	SW 131 Data Rec.	2 SW 1313 Data Rec.
						<u>.</u>	<u>م</u>	B		<u>.</u>	Ø					•	Ø	0	Ø	Ø
LICENCE		P 1101	P 1104			A 1203	A 1292	A 1275			P 1102	A 1434		A 1433	A 1431					
ELECTRICAL	MI 3155 EurotestXD	•	•							•	•									
INSTALLATION	MI 3152 EurotestXC	•	•							•	•									
SAFETY	MI 3152H EurotestXC 2,5 kV	•	•							•	•									
JAILII	MI 3102 BT EurotestXE	•	•***				•				•				•					
	MI 3102H BT EurotestXE 2,5 kV		•***				•				•				•					
	MI 3102H SE EurotestXE 2,5 kV		•***				-								-					
			***				•								•*					
	MI 3100 SE EurotestEASI	•	***								•									
	MI 3125 BT EurotestCOMBO	•					•				•				•					
	MI 3115 PV Anayser NEW	•	•							•	•					_				
	MI 3108 EurotestPV	•	•***				•						•*		•*					
	MI 3109 EurotestPV Lite	•	•***				•						•*							
	MI 3144 Euro Z 800 V	•	•								•									
	MI 3143 Euro Z 440 V	•	•								•									
	MI 3132 EVTester NEW	•	•							•	•									
	MI 3121 Insulation / Continuity						•													
	MI 3121H Insulation / Continuity	/					•													
	MI 3122 Z Line-Loop / RCD						•													
	MI 3123 Earth / Clamp						•													
APPLIANCE	MI 3325 MultiServicerXD	•	•							•	•									
/ MACHINE /	MI 3394 CE MultiTesterXA	•	•							•	•									
SWITCHBOARD	MI 3394 CE MultiTesterXS	•	•							•	•									
SAFETY		•	•							•	•									
541211	MI 3360 OmegaPAT XA	•	•							•	•									
	MI 3309 BT DeltaGT	•	•***			•						•		•						
	MI 3311 GammaGT					•								•*						
	MI 6601 MediTest NEW		•	•						•										
	MI 2893 Power Master XT		-	-	•															
ANALYSIS	MI 2892 Power Master				•															
ANALYSIS	MI 2885 Master Q4				•															
					•															
	MI 2884 Energy Master XA																			
HIGH VOLTAGE	MI 2883 Energy Master MI 3252 MicroOhm 100A				•			•												
INSULATION								•												
	MI 3210 TeraOhmXA 10 kV							•												
/ CONTINUITY	MI 3209 TeraOhmLT 10 kV							•												
/EARTH/	MI 3201 TeraOhm 5 kV Plus							•												
TRANSFORMER	MI 3290 Earth Analyser	•	•							•										
	MI 3288 Earth Insulation Tester		•							•	•									
	MI 3280 DT Analyser	•	•							•										
	MI 3281 WR Analyser	•	•							•										
	in sess step contact system	•	•***					•												
DIGITAL	MD 9060 Digital multimeter																	•		
	MD 9050 Digital multimeter																	•		
CLAMP METERS	MD 9040 Digital multimeter																	•		
	MD 9016 Digital multimeter																•			
	MD 9250 Current clamp																			•
	MD 9240 Current clamp																		•	
	MD 9930 Thermal camera								•											

* Supported by BT dongle. | ** Please contact your local distributor or contact person at Metrel for additional information regarding implementation and distribution of the Metrel SDK. | *** No licence needed.

otes	

lotes	

METREL d.o.o.

Test and Measurement Equipment Ljubljanska 77, SI-1354 Horjul, Slovenia T +386 (0)1 75 58 200 info@metrel.si www.metrel.si

Distributor:





Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery. Subject to technical change without notice.

GUIDELINE_2024_Ang_March